



## THE BASIC IN LINE

### process refractometer

The UR62 digital refractometer is a probe designed for simple installation in-line or in a tank or vessel. It continuously measures concentration and displays and outputs the result in Brix or nD or % concentration with basic accuracy. The UR62 will signal to the process when concentration is outside of specifications or has reached its target end point by means of analogue 4-20 mA output.

The probe is easily set up and configured through a PC or portable computing device using its built in RS485 interface. It can also be connected to the optional RC-24 touch screen operator display unit. The analyzer does not have any drift in the time so that it does not need any adjustment vs the laboratory: after the initial configuration during start up, the operators in the plant do not have to touch the system anymore. Due to the optical technology, the equipment is virtually no maintenance.

#### Benefits

- Optical Technology
- Basic accuracy
- 100% in line installation
- No need of adjustments
- No maintenance

# UR62

PROCESS REFRACTOMETER

BRIX, nD AND % CONCENTRATION OF THE LIQUIDS

## UR62 installation accessories

The UR62 robust construction with stainless steel case and IP67 protection, allows the easy installation using dedicated Maselli adapters directly in the main line.

For specific applications, the refractometer may be equipped with special system for prism cleaning.



## OPERATING SPECIFICATION

Measurement range:	1.3229 ... 1.505 nD(0...85Bx)*
Accuracy:	+/- 0.0004 nD (+/-0.2 Bx) UR62 only +/- 0.0002 nD (+/-0.1 Bx) UR62 with RC24 receiver (IR02)
Measurement scale:	Brix scale or USER scale on request
Repeatability:	+/- 0.2 UR62 only +/- 0.03 UR62 with RC24 receiver (IR02)

\* 0 Bx at max 80°C

## TECHNICAL FEATURES

Product temperature:	-25...+90°C (-13...194°F)
Max sterilization temperature:	hot water at 95°C (203°F) x 30 min, steam (0.5 bar) at 110 °C (230 °F) x 30 min
Line pressure:	max. 10 bar (145 psi) at 20 °C (68 °F) max. 8 bar (116 psi) at 90 °C (194 °F)
Power supply:	AC 24V +/- 10%, 50...60Hz, 80mA DC 24V +/- 10%, 80mA
Interfaces:	Analog, Analog/Digital, PROFIBUS DP, Ethernet/IP
Protection Category:	IP67 to EN60529

Please refer to the technical datasheet for further data.

More products  
For the analysis of  
liquids concentration

**UR24**  
process refractometer  
Ultimate



In Line – Brix / nD

**LR05**  
Laboratory refractometer



Laboratory – Brix / nD/ User Scale



**M maselli**  
PROCESS ANALYZERS

43122 Parma - Italy - Tel. +39.0521.257411  
www.maselli.com

